

## Compact $\phi$ 29mm Machine-Vision Lenses Compatible with 2/3" Imagers and 8-Mega Pixel Resolution

- 2/3" 8mm F/2.4 (Model: MA23F08V)    ■ 2/3" 12mm F/2.4 (Model: MA23F12V)
- 2/3" 16mm F/2.4 (Model: MA23F16V)    ■ 2/3" 25mm F/2.4 (Model: MA23F25V)
- 2/3" 35mm F/2.4 (Model: MA23F35V)    ■ 2/3" 50mm F/2.8 (Model: MA23F50V)

NEW



For

IMX536 2/3" 8-Mega

IMX546 2/3" 8-Mega

IMX566 2/3" 8-Mega

2.74  $\mu$ m

### Main Features

#### > High Resolution and Contrast Unrivaled in the Industry

- Compatible with 2/3" imagers, supporting 2.74 $\mu$ m pixel-pitch and max 8-mega pixel resolution.
- Offer resolution and contrast outperforming other  $\phi$ 29mm machine-vision lenses.

#### > Industry-Leading Low Distortion (TV Distortion)

- Significantly reduce TV distortion compared with previous models.  
(\* MA23F08V: -0.6%, MA23F12V: 0.4%, MA23F16V: -0.05%, MA23F25V: -0.01%, MA23F35V: 0.04%, MA23F50V: 0.05%)

#### > High-Quality Performance at Close-up distances

- A new comprehensive lens design assures high contrast and resolution at commonly used close-up distances.

#### > New Robust Mechanism for Anti-Vibration and Anti-Shock

- A newly designed mechanism improves anti-vibration and anti-shock performance compared with previous models, limiting the optical(image) deflection to less than 10 $\mu$ m even for the severe impact of vibrations and shocks of max 10G of magnitude.




\* [Compliant with IEC 60068-2-6/JIS C 60068-2-6]




Vibration frequency 10-60Hz (amplitude 0.75mm), vibration frequency 60-500Hz (acceleration 100m/S<sup>2</sup>)

#### > A Common-use Setscrew is Attached as a Standard Accessory

- A lock-screw provided with the models can be replaced with any embedding-type setscrew. This further reduces the overall diameter of the lens barrel for more compact installation.

## ■ Specifications

Model	MA23F08V	MA23F12V	MA23F16V
			
Imager Size	2/3"		
Mount Type	C		
Focal Length	8mm	12mm	16mm
Aperture Range	F/2.4 ~ F/16		
Field of View Angle (Horizontal x Vertical)	2/3" (1:1)	53.1°x53.1°	36.0°x36.0°
	2/3" (4:3)	58.9°x45.5°	40.2°x30.6°
Focusing Range	0.1m ~ ∞		
Operation	Focus	Manual w/Lock	
	Iris	Manual w/Lock	
Filter Size	M34 P=0.5mm	M27 P=0.5mm	
Wave Length	Visible Light		
TV Distortion	-0.6% *	0.4% *	-0.05% *
Weight	84g	69g	59g
Operating Temperature	-20°C ~ +60°C		

Model	MA23F25V	MA23F35V	MA23F50V
			
Imager Size	2/3"		
Mount Type	C		
Focal Length	25mm	35mm	50mm
Aperture Range	F/2.4 ~ F/16		F/2.8 ~ F/16
Field of View Angle (Horizontal x Vertical)	2/3" (1:1)	16.9°x16.9°	11.1°x11.1°
	2/3" (4:3)	18.9°x14.3°	12.5°x9.4°
Focusing Range	0.1m ~ ∞	0.2m ~ ∞	0.3m ~ ∞
Operation	Focus	Manual w/Lock	
	Iris	Manual w/Lock	
Filter Size	M27 P=0.5mm		
Wave Length	Visible Light		
TV Distortion	-0.01% *	0.04% *	0.05% *
Weight	55g	58g	74g
Operating Temperature	-20°C ~ +60°C		

\* Design Value

**TAMRON CO., LTD.** <http://www.tamron.biz/en/>  
1385, Hasunuma, Minuma-ku, Saitama-shi, Saitama 337-8556 JAPAN  
Tel: +81-48-684-9129 Fax: +81-48-683-8594

**TAMRON USA, INC.** <http://www.tamron-usa.com>  
10 Austin Boulevard, Commack, NY 11725, USA Tel: +1-631-858-8400 Fax: +1-631-543-3963

**TAMRON Europe GmbH.** <http://www.tamron.de>  
Robert Bosch-Str. 9, 50769 Cologne, GERMANY Tel: +49-221-669544-0 Fax: +49-221-669544-404

**TAMRON INDUSTRIES (HONG KONG) LIMITED** <http://www.tamron.com.hk>  
Unit 908, 9/F, Elite Centre, 22 Hung To Road, Kwun Tong, Kowloon, Hong Kong Tel: +852-2721-7797 Fax: +852-2620-1631

**TAMRON (Russia) LLC.** <http://www.tamron.ru>  
Unikon Business Center 5F No. 9, Plekhanova Street 4a, Moscow, 11123, Russian Federation  
Tel: +7-495-970-0112 Fax: +7-495-970-0112

**TAMRON OPTICAL (SHANGHAI) CO., LTD.** <http://www.tamron.com.cn>  
Room 1707, Ruijin Building, No.205, Maoming South Road, Shanghai, 200020, CHINA  
Tel: +86-21-5102-8880

**TAMRON INDIA PRIVATE LIMITED** <http://www.tamron.in>  
805, 806 & 807 8th floor, Vatika City Point, MG Road, Gurgaon-122001, Hayana, India  
Tel: +91-124-41-168-12 Fax: +91-124-40-822-72



### Management on Quality and Environment :

Tamron is certified with international standards: ISO 9001 for quality and ISO 14001 for environmental management at its Head Office, domestic sales offices, China plant as well as production facilities in Aomori Factory, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations.

● Specifications subject to change without notice